



NO POSN	DIM A
2	19.6 ± 0.3
3	31.6 ± 0.5
4	43.6 ± 0.5
5	55.6 ± 0.7
6	67.6 ± 0.7
7	79.6 ± 0.7
8	91.6 ± 1.0
9	103.6 ± 1.0
10	115.6 ± 1.5
11	127.6 ± 1.5
12	140.7 ± 1.5

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide (PA66), Nature flame-retardant to UL 94-V2

Voltage : 300V (UL) , 500V (VDE)

Current : 35A (UL) , 41A (VDE)

Working Temperature : 105°C (UL) , T110 (IEC)

Terminal Body : Brass, nickel-plated

Wire Protector : Stainless spring steel

Screws : M3.5x7, Steel zinc-plated

Wire Range : 2.5 ~ 6mm² , #22 ~ #10 Sol/Str

International Approvals

UL, VDE, FIMKO, SEMKO, CQC

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

TBT120-W19WP-xx-LF

SERIES

LEADFREE
02~12WAY
WIRE PROTECTOR
HIGH 19.0mm
WIRE TO WIRE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: