

底部 (Base):H型底部, 加高1.2mm
 HOUSING MATERIAL: (NYLON 66, NATURE), UL 94V-2
 WORKING TEMPERATURE: 105°C (UL), T110°C...-30°C (VDE)
 接線排數 (POLES AVAILABLE):12排 (12 POLES)

PART. NO. 編號	mm2 線徑	Amp 安培	Volt. 電壓	Screw 螺絲	尺寸 Dimensions (mm)						Packing 包裝
					A	B	C	D	E	F	
TBT145-WB-xx	16.0	76	500	M4.0x9	169.8	28.00	23.00	14.50	4.20	6.0	10 Pcs/Bag 200 Pcs/Ctn

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
 X, ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

TBT145-WB-xx-LF

SERIES | LEADFREE
 01~12WAY
 BASE 1.2mm
 WIRE TO WIRE

DESCRIPTION: TERMINAL BLOCK (H TYPE) 底部加高1.2mm