



PCB Layout

Pitch : 2.50mm (0.098inch)					
Poles	A(mm)	A(inch)	Poles	A(mm)	A(inch)
2	6.50	0.256	15	39.00	1.535
3	9.00	0.354	16	41.50	1.634
4	11.50	0.453	17	44.00	1.732
5	14.00	0.551	18	46.50	1.831
6	16.50	0.650	19	49.00	1.929
7	19.00	0.748	20	51.50	2.028
8	21.50	0.846	21	54.00	2.126
9	24.00	0.945	22	56.50	2.224
10	26.50	1.043	23	59.00	2.323
11	29.00	1.142	24	61.50	2.421
12	31.50	1.240	25	64.00	2.520
13	34.00	1.339			
14	36.50	1.437			

Current rating : 4Amp 150V  
 Insulation withstands volt : AC1500V min  
 Insulation resistance : >2000MΩ DC500V  
 Operation temperature : -40°C to +105°C  
 Wire range : 20~28 AWG  
 Wire strip length : 6~7mm

CONFIRMED & ACCEPTED BY:

	Material	Plating/Finish	Remark
1	Insulating body	Polyamide 66(UL94V-0)	Grey
2	Cover	Polyamide 66(UL94V-0)	Grey
3	Lever	Grilon AG30	
4	Terminal	Brass	Tin plated
5	Spring	Stainless strip steel	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

照片框

ORDER INFORMATION

TBX025-A15-xx-LF

SERIES

LEADFREE

02~25WAY

HIGH 15.8mm

SLANT DIP

DESCRIPTION: