


P.C.B Layout



Material:

- Item ① Insulating body: Thermoplastic (UL94V-0)
- Item ② Wire guard: PhBz Tin plated.
- Item ③ Insulating lever: Thermoplastic (UL94V-0)
- Item ④ Side Cover: Thermoplastic (UL94V-0)

- ⚠ Electrical:

	cULus	VDE	CQC
● Voltage rating:	300V	130V	300V
● Current rating:	6A	6A	6A
● Wire range:	0.5-0.75 mm ²		
● Solid wire(AWG):	16-20		16-20
● Stranded wire(AWG):	16-20		16-20
- ⚠ ● Wire strip length: 8.5-9.5mm
- Withstanding Voltage: 1.6KV 1.25KV 1.6KV
- ⚠ ● Operating temperature: -40°C to +115°C
- ⚠ ● Soldering temperature: 250°C ±10°C/5 Sec
- ⚠ ● Safety Approval:

--	--	--

POLE		2	3	4	5	6	7	8	9	10	11	12	
A		8.50	12.00	15.50	19.00	22.50	26.00	29.50	33.00	36.50	40.00	43.50	
B		3.50	7.00	10.50	14.00	17.50	21.00	24.50	28.00	31.50	35.00	38.50	
Tol.		±0.10						±0.15					
POLE		13	14	15	16	17	18	19	20	21	22	23	24
A		47.00	50.50	54.00	57.50	61.00	64.50	68.00	71.50	75.50	78.50	82.00	85.50
B		42.00	45.50	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	77.00	80.50
Tol.		±0.20						±0.30					

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

TBX035-A12L1-xx-LF

SERIES
LEADFREE
02-24 WAY
L TYPE FOOT
HIGH 12.9mm
SLANT DIP

DESCRIPTION: