



- Material:
- Item A Terminal lever: Thermoplastic (UL94V-0) Orange(RAL 2011/P)
  - Item B Terminal top housing: Thermoplastic (UL94V-0)
  - Item C Female contact : PhBz Tin Plated.
  - Item D Spring clamp : Stainless steel
  - Item E Terminal down housing: Thermoplastic (UL94V-0)
- Electrical: cULus
- Voltage rating: 160 V
  - Current rating: 5.5 A
  - Wire range:
  - Solid wire(AWG): 16-24
  - Stranded wire(AWG): 16-24
  - Wire strip length: 9-10 mm
  - Withstanding Voltage: 1.32 KV
  - Operating temperature: -40°C to +115°C
  - APPROVAL:

$$\text{DimL} = (N-1) \times 3.5 + 4.2$$

$$\text{DimP} = (N-1) \times 3.5$$

N=Number of poles

POLES	Dim.	
	Tol	Dim.L/P
2p-6p		±0.15
7p-12p		±0.25
13p-18p		±0.30
19p-24p		±0.40

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY X. ± 0.50  
 .X ± 0.30  
 CHECKED BY GENIUS .XX ± 0.10  
 .XXX ±  
 UNIT / mm SCALE 1 : 1 .ANG ± 1°

煜倫股份有限公司

www.morethanall.com

DATE  
 SIZE A4 PPROJECTION

照片框

ORDER INFORMATION

TBX035-SVCA-xx-LF  
 SERIES LEADFREE  
 02-24WAY  
 A TYPE  
 CAGE  
 SCREW 180°  
 FEMALE

DESCRIPTION: