



P.C.B. LAYOUT(REF)

NOTES:

1. Rating: 300V 15A (IEC 450V)
PITCH: 5.00mm
2. Insulation Withstands Voltage:
AC 1500 V/MIN
3. Insulation Resistance:
500M Ω or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
5. Suitable Electric Wire:
AWG 28~12 (IEC 0.5~2.5mm²)
6. Undimensioned Tolerances:

—	∩	∇	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONS TOLERANCES			±0.3

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
4	SOLDER PIN		P/2	COPPER	Tin Plated
3	SOLDER PIN		P/2	COPPER	Tin Plated
2	CLAMP		P	Stainless Steel	
1	HOUSING		P/2	PA66(V0)	M001

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

TBY050B06-A26-xx-LF

SERIES

LEADFREE
02-24WAY
HIGH 26.7mm
SLANT DIP

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com