



P.C.B. LAYOUT(REF)

NOTES:

1. Rating: 300V 10A(IEC 450V)
PITCH: 5.00mm
2. Insulation Withstands Voltage:
AC 1500 V/MIN
3. Insulation Resistance:
500M Ω or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
5. Suitable Electric Wire:
AWG 28~12 (IEC 0.5~2.5mm²)
6. Undimensioned Tolerances:

—	∩	∇	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONED TOLERANCES			±0.3

7	SOLDER PIN	0119B00600	P/4	COPPER	Tin Plated
6	SOLDER PIN	0119B00500	P/4	COPPER	Tin Plated
5	SOLDER PIN	0119B00700	P/4	COPPER	Tin Plated
4	SOLDER PIN	0119B00800	P/4	COPPER	Tin Plated
3	CLAMP	X000003100	P	Stainless Steel	
2	END COVER	0119P5XX00	1	PA66(V0)	M001 GREY
1	HOUSING	0119N6XX00	P/4	PA66(V0)	M001 GREY
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

TBY050D1-D44R-xx-LF

SERIES

LEADFREE

04~96WAY

4 ROW

DIP 4.0mm

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com