



P.C.B Layout
Top view

Material:

- Item ① Terminal body: Thermoplastic (UL94V-0)
- Item ② Terminal side body: Thermoplastic (UL94V-0)
- Item ③ Terminal cover: Thermoplastic (UL94V-0)
- ▲ Item ④ Contact pin : Copper, Tin Plated.
- Item ⑤ Contact pin : Copper, Tin Plated.
- Item ⑥ Spring clamp : Stainless steel

- ▲ Electrical: cULus
- Voltage rating: 300 V
- Current rating(Sol): 30 A
- Current rating(Str): 35 A
- Solid wire(AWG): 10-24
- Stranded wire(AWG): 8-24
- Wire strip length: 15-16 mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +120°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- Critical dimension:

N=NUMBER OF POLES

DIM	TOL			
	1P--5P	7P--11P	13P--15P	
Dim P	(N-1)×7.5	±0.15	±0.25	±0.35
Dim L	N×7.5+1.8	±0.15	±0.25	±0.35

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm

SCALE 1:1

DATE

SIZE A4

X. ± 0.50

.X ± 0.30

.XX ± 0.10

.XXX ±

ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

TBY075-R20L-xx-LF

SERIES

LEADFREE
01-15 POLES
L TYPE FOOT
HIGH 20.2mm
DIP 90°

DESCRIPTION: