


MATERIAL AND FINISH:

NO.	DESCRIPTION	MATERIAL	FINISH
1	HOUSING	LCP	COLOR:BLACK
2	CONTACT	COPPER ALLOY	CONTACT AREA: AU
3	SWITCH A[Vss]	COPPER ALLOY	
4	SWITCH B[Vdd]	COPPER ALLOY	
5	PLATE	SUS	FLAT AREA: Au_OR_SN
6	SLIDER	LCP	COLOR:BLACK
7	COIL SPRING	SUS	
8	LOCK PIN	SUS	

PIN NO.	DESCRIPTION
# 1	DAT2
# 2	DC/DAT3
# 3	CMD
# 4	VDD
# 5	CLK
# 6	VSS
# 7	DAT0
# 8	DAT1
# 9	ANT1
# 10	ANT2

CIRCUIT OF SWITCHES:



Notes :

1. There is no problem in the quality to remain some lubricant on the surface of products.
2. There is a possibility of changing about detailed shape and materials.
3. The shaded portion in figure shows the range of operation of the switch[vss] When the card is inserted, please install the clearance of 0.3mm to avoid electric contact.
4. The diagonal area in drawing is a pattern prohibition area, separately, make a arrangement for details.
5. Coplanarity of contacts and plate are 0.1MAX.

RoHS Compliant




煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

TOLERANCES ARE

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

TFC-WPBE14A-08-LF
 SERIES | | | | | LEADFREE
 | | | | | 08WAY
 | | | | | A TYPE
 | | | | | EAR TO EAR 14.3mm
 90°SMT | | | | | BOTTOM CONTACT
 | | | | | PUSH PUSH

DESCRIPTION: Micro SD Socket