

8	RING	BRASS	NICKEL	1
7	GASKET	RUBBER	RED	1
6	WASHER	BRASS	NICKEL	1
5	WASHER	STEEL	NICKEL	1
4	PIN	BRASS	GOLD	1
3	INSULATOR	PLASTIC	WHITE	1
2	BODY	BRASS	NICKEL	1
1	SHELL	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

ELECTRICAL SPECIFICATIONS:

IMPEDANCE: 50 OHM

FREQUENCY RANGE: 0-4 GHz

WORKING VOLTAGE: 500 VRMS MAX

DIELECTRIC WITHSTANDING: 1500 VRMS MIN

INSULATION RESISTANCE: 5,000 MEGOHMS MIN


CONTACT RESISTANCE:

CENTER CONTACT 3 MILLIOHMS MAXIMUM.

OUTER CONTACT 2 MILLIOHMS MAXIMUM.

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

- X. ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

PJECTION

照片框

ORDER INFORMATION

TNC-PC-400-LF
 SERIES | LEADFREE
 LMR400
 CRIMP
 MALE

DESCRIPTION: TNC MALE CRIMP LMR400

煜倫股份有限公司

www.morethanall.com