



SCHEMATIC

P.C.B. MOUNTING HOLE

TRSW-RxGS-1X03-LF



MODEL NO.	SWITCHING POSITION		
1	ON		ON
2	ON		(ON)
3	ON	OFF	ON
Term. Comm.	2-3	OPEN	2-1

SPECIFICATION

Rating: 3A @ 120V AC or 28V DC
 1A @ 250V AC or 0.4A @ 20V AC or DC.
Electrical life: 30,000 make-and-break cycles at full load.
Contact resistance: 20mΩ Max. Initial @2-4V DC.
 100mA, for both silver and gold plated contacts.
Insulation resistance: 1,000MΩ Min.
Dielectric strength: 1,000V RMS @ sea level.
Operating temperature: -30°C ~ +130°C.
Soldering temperature: 250°C Max for 3 Sec.

MATERIAL

Case: Diallyl phthalate (DAP)(UL-94V-0).
Actuator: Nylon, black standard.
Bushing: Brass, nickel plated.
Housing: Stainless steel.
Terminal/contact: Brass, with silver or gold plated.
Switch support: Brass, tin plated.

RoHS Compliant



PART NO. TRSW-RxGS-1X03

DWG NO. TRSW-RxGS-1X03

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION: **Toggle Switch**

FILE NO.

DRAWING BY

.X ± 0.2
.XX ± 0.1
.XXX ±
AWG

AREA

REVISIONS

HK

DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION