



4.	PLASTIC HOOD COLOR BLACK.
3.	USB CONN.: B TYPE,MALE,SOLDER TYPE, GOLD-FLASH. INSULATOR: PBT, WHITE. FRONT SHELL Ni-PLATED, BACK SHELL Ni-PLATED. WITH SPRING.
2.	USB CONN.: A TYPE, MALE, SOLDER TYPE, GOLD-FLASH. INSULATOR: PBT, WHITE. SHELL: NI-PLATED.
1.	CABLE: UL2725 28AWGx1P+28AWGx2C+AEB. PVC JACKET BLACK. OD=ø3.5±0.1mm.
NO.	NOTES:

WIRE ARRANGEMENT		
P1	COLOR	P2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
CASE	BRAID SHIELD	CASE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UBX2-4A4B28-M1F-LF

SERIES

LEADFREE

305mm

MALE TO MALE

28 AWG

4 PIN A TYPE TO 4 PIN B TYPE

DESCRIPTION: