


WIRING DIAGRAM



4	CORE	2	PCS	RH 12(OD)*6.5(ID)*L20mm
3	CONN.	1	PCS	USB B MALE SOLDER
2	CONN.	1	PCS	USB A MALE SOLDER
1	CABLE	2000	mm	UL2725 28AWG*1P(WHITE, GREEN)+24AWG*2C (RED, BLACK)+AEB OD:4.5mm #GRAY RE2.0
NO.	PART NO.	Q'TY	UNITS	DESCRIPTION

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

ORDER INFORMATION

UBX2-4A4B2VFC2-M2M-LF  
SERIES | LEADFREE  
2000mm  
MALE TO MALE  
FERRITE CORE x2  
2.0 REV  
4 PIN A TYPE TO 4 PIN B TYPE

DESCRIPTION: USB A M / B M / 2M / CORE / BEIGE