



**MATERIAL LIST:**

④	UOTER MOLD	PVC 45P 黑色	1
③	INNER MOLD	PE内模料 透明	1
②	CONNECTOR	USB3.0 AM 壳镍 PIN金G/F 兰胶芯	2
①	CABLE	USB3.0 28+28+24AWG OD:5.5 BLACK [(7/0.12TC*1P+7/0.12TC+AL/MY)*2C+7/0.12TC*1P+7/0.20TC*2C +填充+AL+7/0.12BC+16*8/0.12AL]*1C	1
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y

**NOTES:**

1. 100%% OPEN & SHORT TEST
2. CONDUCTIVE RESISTANCE : 5 OhmsMAX
3. INSULATION RESISTANCE : 5M OhmsMIN
4. HI-POT : 300V DC/10ms
5. The product is HSF compliant.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.25  
.XX ± 0.15  
.XXX ± 0.05  
ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

UBX2-9A9A28-M1M9-LF

SERIES | LEADFREE  
1900mm  
MALE TO MALE  
28 AWG  
9 PIN A TYPE TO 9 PIN A TYPE

DESCRIPTION: