



USB3.0 AM	USB3.0 BM	COLOR
1	1	RED(PWR)
2	2	WHITE(UTP_D-)
3	3	GREEN(UTP_D+)
4	4	BLACK(GND_PWRrt)
5	5	YELLOW(SDP1-)
6	6	BLUE(SDP1+)
7	7	DRAIN(SDP1_Drain) (SDP2_Drain)
8	8	ORANGE(SDP2-)
9	9	PURPLE(SDP2+)
		SHELL — SHELL — Braid

ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm
3. Insulation Resistance:5Mega ohm
4. Hipot test:DC 300V/10ms

USB3.0

QTY	DESCRIPTION	UNIT
4	55P PVC MOLD BLUE IN COLOR	pcs
3	USB3.0 B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	pcs
2	USB3.0 A TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	pcs
1	UL20276 (1P*28#+D+AL+Myair)*2C+1P*28#+2C*28#+AL+B DD:5.5±0.15mm BLUE IN COLOR	pcs

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



**ORDER INFORMATION**

UBX2-9A9B28-M1M-LF

SERIES

LEADFREE

1000mm

MALE TO MALE

28 AWG

9 PIN A TYPE TO 9 PIN B TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: USB3.0-AMBM-100BU