

SPECIFICATION

MATERIAL

Insulator: PBT, rated UL94V-0 (standard)
Contacts: Brass (Male) ; Phosphor Bronze (Female)
Rivet,Boardlock: Copper alloy

CONTACT PLATING

Underplate: 50m² Nickel
Contact area: 1m²~30m² Selective gold
Solder tails area: 100m² Tin/Lead

ELECTRICAL

Operation voltage: 250 VAC max.
Current rating: 3 Amps max.
Contact resistance: 20 mohms max.
Insulation resistance: 3000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 1000 VAC / minute
Operating temperature: -55°C TO +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

X, ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20


DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

UC-PRZ-3X16-LF
SERIES | CLIP | LEADFREE
48 WAY
DIP 90°
MALE

DESCRIPTION:

www.morethanall.com