



RECOMMENDED P.C.B LAYOUT(TOP VIEW)
TOLERANCES: ±0.05mm

MATERIAL
 Insulator: Thermal Plastic UL94V-0
 Contacts: Copper Alloy
 Rivet,Boardlock: Copper Alloy
CONTACT PLATING
 Underplate: 50u"~100u" Nickel
 Contact Area: 1u"~30u" Selective Gold
 Solder Tails Area: 100u"~200u" Tin(Lead Free)

ELECTRICAL
 Operation Voltage: 250 VAC Max.
 Current Rating:

TEMP(°C)	20	70	100
CURRENT	2.0A	1.8A	1.0A

Contact Resistance: 20 mohms Max.
 Insulation Resistance: 3000 Mohms Min. @ 500 VDC
 Dielectric Withstanding Voltage: 1000 VAC / Minute
 Temperature Range: -55°C TO +125°C

NOTE:

PART NO.	A	B	C
UC-SRZ-3X32	88.90	94.00	85.00
UC-SRZ-3X16	48.26	54.30	44.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

UC-SRZ-3Xxx-LF
 SERIES | LEADFREE
 3X16:48 WAY
 3X32:96 WAY
 CLIP
 DIP 90°
 FEMALE

DESCRIPTION: