





Dip Type



P.C. Board Layout (Power)

Material:

Housing: Thermoplastic Polyester Glass Filled UL94V-0.

Contacts: Copper Alloy.

Power: Copper Alloy.

Electrical Characteristics:

Current Rating: 2 AMP.

Dielectric Withstanding Voltage: AC 1000V For 1 minute.

Insulator Resistance: 1000MΩ min. at DC 500V.

Contact Resistance: 20mΩ max. at DC 100mA.

Operating Temperature: -55°C ~ +125°C .

*RoHS Compliant

Current Rating(A)	10A	20A	30A	40A
Dimension(øP)	2.10	3.25	3.57	4.15
Length	04	02	13	17
X	4.0	2.5	13	17
Dimension				
A	(2.54 x No of Contact)/3-2.54			
B	(7.62 x No of Coaxial)/2-7.62			
Pitch	Position	Rows with Contacts	Contact Arrange	With Power
2.54mm	78	a b c	c- b- a- 4 5 6 7	2 Pcs
	60	a b c	c- b- a- 7 8 9 10	4 Pcs
	42	a b c	c- b- a- 10111213	6 Pcs
	24	a b c	c- b- a- 13141516	8 Pcs
	6	a b c	c- b- a- 16171819	10 Pcs
	52	a - c	c- b- a- 4 5 6 7	2 Pcs
	40	a - c	c- b- a- 7 8 9 10	4 Pcs
	28	a - c	c- b- a- 10111213	6 Pcs
	16	a - c	c- b- a- 13141516	8 Pcs
	4	a - c	c- b- a- 16171819	10 Pcs

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.25

.XX ± 0.15

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UM-PDxx-xx+x-LF

SERIES

LEADFREE

MALE

DIP 180°

04+10

78+2

04:4.0mm

02:2.5mm

13:13.0mm

17:17.0mm

DESCRIPTION: