



## SPECIFICATIONS:

CURRENT RATING: 1.0A AC,DC  
 VOLTAGE RATING: 500V AC,DC  
 CONTACT RESISTANCE: 30m OHM MAX.  
 INSULATION RESISTANCE: 1000M OHM MIN.  
 WITHSTANDING VOLTAGE: 750V AC/MINUTE  
 TEMPERATURE RANGE: -25°C TO +125°C  
 Mating cycle : 5000 cycles min.

## MATERIALS:

CONTACT:BRASS  
 INSULATOR: Nylon 6T. UL 94V-0.  
 CONTACT:GOLD PLATED  
 SHELL:NICKEL FLASH

## Method Test:

Insertion force rating:1.0~2.0kg/pc  
 Withdrawal force rating:0.8~2.0kg/pc

PCB LAYOUT

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±

ANG±

照片框

ORDER INFORMATION

USB-PWP4-4A-LF  
 SERIES | LEADFREE  
 4 PIN A TYPE  
 POSTx4  
 90°SMT  
 MALE

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION:USB A TYPE SMD