



- NOTES:
- 1.MATERIAL:
 - 1.1 Housing:PBT ,UL94-HB
 - 1.2 terminals:Copper Alloy
Gold plated in contact area:
Tin 40u"min plated in termination
Nickel Plated overall
 - 1.3 Shell:SPCC or Brass t=0.30mm,
Nickel 40u"min Plated overall
 - 2.ELECTRICAL CHARACTERISTICS:
 - 2.1 Rating Current :1.5 Ampere
 - 2.2 Rating Voltage :30 V Max
 - 2.3 Contact Resistance:30 Milli ohms
 - 2.4 Insulation Resistance:1000 Mega ohms Min.
 - 3.MECHANICAL CHARACTERISTICS:
 - 3.1 Connector Mating force: 35N MAX(3.57Kgf)
 - 3.2 Connector Unmating force:10N min(1.02Kgf)
 - 3.3 Durability:1500Cycles.
 - 4.ENVIRONMENT CHARACTERISTICS:
 - 4.1 Operating temperature:-0℃ to +50℃
 - 4.2 Storage temperature:-20℃ to +60℃

RoHS Compliant

TOLERANCES ARE

照片框

ORDER INFORMATION

USB-SDBK-4B-LF
 SERIES | | | LEADFREE
 | | | 4 PIN B TYPE
 | | | BLACK
 | | | DIP 180°
 | | | FEMALE

DESCRIPTION: USB BF 180度彎腳 L:21.7

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY		X. ± .X ± 0.25 .XX ± 0.15 .XXX ± 0.05 ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	