


Note:

Specification:

1. Rated voltage and current: 1.5A at 250V AC minimum.
2. Dielectric withstanding voltage: 500V AC/1 minute without breakdown.
3. Contact resistance: Before life test 30m ohm max, After life test 50m ohm max.
4. Insulation resistance: 1000M ohm min.
5. Insertion force: 35 Newtons maximum.
6. Extraction force: 10 Newtons minimum.
7. Durability : 1500 cycles.
8. Solderability: Terminal shall be immersed in flux before text, Then dip in molten solder for 5±0.5 sec. At 245±5°C.
9. Temperature range: -55°C~+85°C



3	Shell	1	Steel	T=0.30mm	80u" min. Nickel Plated
2	Contact	4	Brass	T=0.25mm	Contact area:0.8u" min. Gold Plated over 40u"Nickel min. Solder area:80u" min. matte Tin Plated over 40u"Nickel min.
1	Housing	1	P.B.T	UL 94-V0	Black/White
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ± 1°

PPOJECTION



ORDER INFORMATION

USB-SRxx-4A-LF

SERIES | LEADFREE  
4 PIN A TYPE  
FEMALE | BK:BLACK  
WH:WHITE  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: USB-A(F)90°DIP(外殼弧腳)外殼鐵料