



Note:

Specification:

1. Rated voltage and current: 1A at 250V AC minimum.
2. Dielectric withstanding voltage: 500V AC/1 minute without breakdown.
3. Contact resistance: Before life test 30m ohm max, After life tset 50m ohm max.
4. Insulation resistance: 1000M ohm min.
5. Insertion force: 35 Newtons maximum.
6. Extraction force: 10 Newtons minimum.
7. Solderability: Terminal shall be immersed in flux before text, Then dip in molten solder for 5±0.5 sec. At 245±5°C.

3	Shell	1	Brass	T=0.30mm	80u"min Nickel Plated
2	Contact	4	Brass	T=0.25mm	Contact area:0.8u"min Gold Plated over 40u"Nickel min. Solder area:80u"min Tin Plated over 40u"Nickel min.
1	Housing	1	△PA9T	UL 94-V0	Black/Ivory
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

PJECTION

照片框

ORDER INFORMATION

USB-SWEPxx-4A-LF
SERIES | | | | LEADFREE
4 PIN A TYPE
FEMALE | | | | POST
90°SMT | | | | EAR
BK:BLACK
WH:WHITE

DESCRIPTION: USB-A(F) S.M.T(外殼SMT)