



SPECIFICATIONS

Current Rating: 7A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
VH-DEE-02	7.92	11.88
VH-DEE-03	15.84	19.80
VH-DEE-04	23.76	27.72
VH-DEE-05	31.68	35.64
VH-DEE-06	39.60	43.56
VH-DEE-07	47.52	51.48
VH-DEE-08	55.44	59.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 ANG ±

照片框

ORDER INFORMATION

VH-DEE-xx-LF
 SERIES | LEADFREE
 | 02-08 WAY
 | EMPTY EVEN 2.46.. PIN
 | DIP 180°

DESCRIPTION: 7.92mm PITCH 180° WAFER