



PCB LAYOUT TOP VIEW

SCALE 2:1 ALL TOL.±0.05

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. Waterproof Rate : IP67.
2. Panel Thickness : 0.8 to 4.0 mm.
3. HEX NUT TORQUE: 2.5~3kgf-cm TIGHTENING TORQUE.

WMJ-RPB-0808-LF
LEADFREE
RoHS Compliant

RJ45 SHIELDED		
Pin	Name	Function
1	TX D1+	TRANCEIVE DATA+
2	TX D1-	TRANCEIVE DATA-
3	RX D2+	RECEIVE DATA+
4	BI D3+	BI DIRECTIONAL DATA+
5	BI D3-	BI DIRECTIONAL DATA-
6	RX D2-	RECEIVE DATA-
7	BI D4+	BI DIRECTIONAL DATA+
8	BI D4-	BI DIRECTIONAL DATA-

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. WMJ-RPB-0808		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION: SIZE 3 RJ45,PLASTIC LOCK,PANEL,DIP 90°		
DWG NO. WMJ-RPB-0808						
FILE NO.		DRAWING BY	AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1:1	PROJECTION				