



Description:

1Features:

Waterproofgrade: IP66~IP68 (temporaryinvasiondidnot, thebiggest extremepressure1.3psior1mwaterdepth)

Ratedvoltage: 500VACMIN

Ratedcurrent: 5A

Contact resistance: 30mΩ MAX.

Insulation resistance: 5000MΩ MIM. at 500V DC

Ratedvoltage: 500VACRMSfor1Minute

Temperature range: -55°C ~ +105°C

Wirecorerange: 22AWG~26AWG

(2)Material:

Plasticcore: PBT+30G. F (UL94V-0)-WH

CarPIN: C3604 (BRASS), gold-plated1U", 3u", 10u", 15u", 30u", 50u"

IronShell: SPCC, nickel-plated

3Note:

a. encollagecannothavebubbles, gluesepagephenomena.

b. spraytested48Hcannothaveoxidationrusting.

c. Finishednothaveacurvedneedle, Rangularinconsistenciesand otherundesirable.

PIN	A	B	C
9	39.40	24.99	16.33
15	47.72	33.32	24.66
25	61.44	47.04	38.38
37	77.9	63.50	54.84

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

WPDB-SSNH-xx-LF

SERIES | | | | LEADFREE
09-37WAY
HEX SCREW
NUT
SOLDER
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DB面板型防水连接器系列圖