



PCB Layout

1. Material And Finish:

Shell: Steel, Front Shell Tin Finished,
Back Shell Tin Finished,
Dimples On Plug Only

Insulator: PBT+30% Glass Filled, Thermoplastic, UL 94V-0,Black

Contacts: Copper Alloy, Full Gold Flash

Sealing Compound: EPOXY

2. Specification:

Contact Current Rating: 3.0 A

Contact Resistance: 10mΩ Max.

Dielectric Withstanding Voltage: 1000 V AC Min.

Insulator Resistance: 5GΩ Min.

Temperature Range: -25°C ~ +85°C

Degree Of Protection: IP67 According To IEC60529

No.	A	B	C	D	E
15	16.92	24.99	30.81	2.29	1.145
26	25.25	33.32	39.14	2.29	1.145
44	38.96	47.04	53.04	2.29	1.145
62	55.42	63.50	69.32	2.41	1.205

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.25
.XXX ± 0.15
ANG ± 2°

PPOJECTION

照片框

ORDER INFORMATION

WPHD-PRZN-xx-LF

SERIES
LEADFREE
15-62 WAY
NUT
CLIP
DIP 90°
MALE

DESCRIPTION: D-SUB 90°, MALE, L PIECE, 8.89 mm, Machine Pin