


34.50<u>1c</u> 13.30 16.70



MATERIALS:


PLASTIC HOUSING: ENGINEERING THERMOPLASTIC FLAMMBILITY RATING UL 94V-0.


CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT.

Nut:ENGINEERING THERMOPLASTIC FLAMMBILITY RATING UL 94V-0.

Gasket: EPDM





Panel Thick:1.5~2.0mm

		R
_AAORETH	IANAI	L
PCB CONN Cable AS	NECTORS SEMBLIE:	s
煜倫股份有	限公司	司

RoHS Compliant		TOLERANCES ARE	
1/ORETHANALL	DRAWING	BY CY	X. ±
PCB CONNECTORS Cable ASSEMBLIES	CHECKED BY GENIUS		.X ± .XX ±
命股份有限公司	UNIT / mm	SCALE 1:1	.XXX ± ANG ±
用股份有限公司	DATE		ANG ±
www.morethanall.com	SIZE A4	PPOJECTI	ON (Q C

照片框

ORDER INFORMATION				
WRJX2-F SERIES	APB-0808-LF LEADFREE 8P8C PANEL BACK ASSEMBLY			
F	EMALE			

DESCRIPTION: 防水接頭(盒端加JACK)