



**SPECIFICATIONS**

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$   
 Contact Resistance: 10m $\Omega$  Max  
 Insulation Resistance: 1000M $\Omega$  Min  
 Withstanding Voltage: 1000V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

Circuit No.	Dimensions			
	A	B	C	D
02P	2.50	5.70	7.20	3.00
03P	5.00	8.20	9.70	3.00
04P	7.50	10.70	12.20	5.30
05P	10.00	13.20	14.70	6.50
06P	12.50	15.70	17.20	6.50
07P	15.00	18.20	19.70	10.30
08P	17.50	20.70	22.20	10.30
09P	20.00	23.20	24.70	10.30
10P	22.50	25.70	27.20	15.30
11P	25.00	28.20	29.70	15.30
12P	27.50	30.70	32.20	15.30
13P	30.00	33.20	34.70	15.30
14P	32.50	35.70	37.20	15.30
15P	35.00	38.20	39.70	15.30
16P	37.50	40.70	42.20	15.30

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X,  $\pm$   
 .X  $\pm$  0.25  
 .XX  $\pm$  0.15  
 .XXX  $\pm$  0.05  
 ANG  $\pm$

照片框

**ORDER INFORMATION**

XHL-H-xx-LF  
 SERIES | LEADFREE  
 02~16WAY  
 HOUSING

DESCRIPTION: 2.50mm PITCH HOUSING