



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	2.50	7.50	11P	25.00	30.00
03P	5.00	10.00	12P	27.50	32.50
04P	7.50	12.50	13P	30.00	35.00
05P	10.00	15.00	14P	32.50	37.50
06P	12.50	17.50	15P	35.00	40.00
07P	15.00	20.00			
08P	17.50	22.50			
09P	20.00	25.00			
10P	22.50	27.50			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY		X, ± .X ± 0.25 .XX ± 0.15 .XXX ± 0.05 ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	P PROJECTION	



ORDER INFORMATION

XHL-R-xx-LF
 SERIES | LEADFREE
 02~15WAY
 DIP 90°

DESCRIPTION: 2.50mm PITCH 90° WAFER