

XH 2.5-5P
P1

XH 2.5-5P
P2

XHX2-0505R1-FN27C-LF
LEADFREE

WIRING DIAGRAM

| P1 | P2 | |
|----|----|--------|
| 1 | 1 | RED |
| 2 | 2 | YELLOW |
| 3 | 3 | SCREEN |
| 4 | 4 | GREEN |
| 5 | 5 | BLUE |

RoHS Compliant

| 7 | | | | |
|-----|----------|------|-------|----------------------------------|
| 6 | | | | |
| 5 | TUBE2 | 1 | PCS | ø1.0mm*8mm |
| 4 | TUBE1 | 1 | PCS | ø4.0mm*10mm |
| 3 | HOUSING | 2 | PCS | XH 2.5-5P |
| 2 | TREMINAL | 10 | PCS | XH 2.5-T |
| 1 | CABLE | 0.3 | M | UL2464 28AWG 4C+AEB #BK OD:3.5mm |
| NO. | PART NO. | Q'TY | UNITS | DESCRIPTION |



PART NO. XHX2-0505R1-FN27C

DWG NO. XHX2-0505R1-FN27C

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

XH 2.5-5P/5P

FILE NO.

UNIT / mm

DRAWING BY

.X ± 0.2
.XX ±
.XXX ±
AWG

AREA

REVISIONS


HK

DATE

焜倫股份有限公司

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE