


Recommended P.C.B Layout
(Tolerance:±0.05)



Materials


Contact Material: Phosphor Bronze
Insulation Material: Polyester, UL 94V-0
Nylon 6T

Specifications

Current Rating: 1Amp
Insulation Resistance: 1000MΩ Min.
Dielectric Withstanding: 300V AC/DC
Contact Resistance: 20mΩ Max.

Operating Temperature:

Gold plating: -40°C to +105°C



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.15
.XXX ±
ANG ± 3°

PPOJECTION

照片框

ORDER INFORMATION

YA-V36XC-1XxxR-LF
SERIES
180°SMT
HIGH 3.6mm
CAP
NON POST
LEADFREE
R TYPE FOOT POSITION
1X02:02WAY
1X40:40WAY

DESCRIPTION: FEMALE HEADER 1.27*1.27mm SMT TYPE, TOP ENTRY HEIGHT 3.4mm CAP+T/R