



P.C.B. LAYOUT

MATERIAL
HOUSING : NYLON 6T,UL94V-0
CONTACT : PHOSPHOR BRONZE
PLATED : GOLD-FLASH
COLOR : BLACK

SPECIFICATION
CURRENT : 1A
OPERATING TEMPERAURE : -40 C TO +105 C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE: 5000 MEGAOHMS MIN
WITHSTAND VOLTAGE : 500 V AC MIN

CONTACTS	A	B
2X3	4.21	2.54
2X4	5.48	3.81
2X5	6.75	5.08
2X6	8.02	6.35
2X7	9.29	7.62
2X8	10.56	8.89
2X9	11.83	10.16
2X10	13.10	11.43
2X11	14.37	12.70
2X12	15.64	13.97
2X13	16.91	15.24
2X14	18.18	16.51
2X15	19.45	17.78
2X16	20.72	19.05
2X17	21.99	20.32
2X18	23.26	21.59
2X19	24.53	22.86
2X20	25.80	24.13
2X21	27.07	25.40
2X22	28.34	26.67
2X23	29.61	27.94
2X24	30.88	29.21
2X25	32.15	30.48

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

YAX-V46P-2Xxx-LF

SERIES

LEADFREE

2X03:06WAY

2X25:50WAY

POST

HIGH 4.6mm

180°SMT

DESCRIPTION: