



PART NO	A±0.20	B±0.20	C±0.20	D±0.20
CS-P-14	38.80	30.20	25.60	12.96
CS-P-24	49.30	40.20	36.47	23.76
CS-P-36	62.00	53.50	49.35	36.72
CS-P-50	77.40	68.30	64.47	51.84

Note:

1. Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass, T=0.20mm.
- 1.3 Front shell: Cold rolled steel, t=0.45mm, 0.50mm, 0.60mm
- 1.4 Back shell: Cold rolled steel, t=0.40mm.

2. Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3. Finishes:

- 3.1 Contacts: Gold flashed 1u", 3u", 5u", 10u", 15u", 30u".
- 3.2 Shell: Nickel, tin or gold plated

4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-shell	1	Cold Rolled Steel	T=0.45mm, 0.50mm, 0.60mm	Nickel Plated
2	Contact	14~50	Brass	T=0.20mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/Blue/White
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°



ORDER INFORMATION

CS-P-xx-LF
SERIES | LEADFREE
14~50 WAY
MALE

DESCRIPTION: CENTRONIC SOLDER傳統

www.morethanall.com