

SPECIFICATIONS

Electrical

Current Rating: 1A AC, DC
 Voltage Rating: 150V AC/ max.
 Operating Temp.: -25°C ~ +85°C
 Insulation Resistance: 500MΩ/ min.
 Withstand Voltage: 500V AC/ min.
 Contact Resistance: 30mΩ/ max.

Material

Terminal Material: Brass/ Tin-plated
 Material: Nylon 6T, UL94V-0

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
20	23.75 (0.935)	30.00 (1.181)	DF14-WX-20	
25	30.00 (1.181)	36.25 (1.427)	DF14-WX-25	
30	36.25 (1.427)	42.50 (1.673)	DF14-WX-30	

RoHS Compliant

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm

SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION



ORDER INFORMATION

DF14-WX-xx-LF

SERIES | LEADFREE
 20.25.30WAY
 NON POST
 90°SMT

DESCRIPTION: 1.25mm Wire-to-Board Header SMT 90° Type