



NO POSN	DIM A
2	16.6 ± 0.3
3	26.6 ± 0.5
4	36.6 ± 0.5
5	46.6 ± 0.7
6	56.6 ± 0.7
7	66.6 ± 0.7
8	76.6 ± 1.0
9	86.6 ± 1.0
10	96.6 ± 1.0
11	106.6 ± 1.5
12	117.2 ± 1.5

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide 66 (PA66), Nature flame-retardant to UL 94V-2

Voltage : 300V (UL), 450V (VDE)

Current : 30A (UL), 32A (VDE)

Working Temperature : T110 (IEC), 105° C (UL)

Insert : Brass, nickel-plated

Screws : M3.0x6, Steel zinc-plated

Wire Range : 1.0 ~ 4.0mm², #22 ~ #10 Sol. #14 ~ #10 Str.

International Approvals

UL, CSA, CE, VDE, FIMKO, SEMKO, NEMKO, DEMKO, KEMA, OVE, CEBC, SEV, CQC, IMQ

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.4
.XX ± 0.2
.XXX ±
ANG ±



ORDER INFORMATION

TBT100-WB-xx-LF

SERIES

LEADFREE

02~12WAY

BASE

WIRE TO WIRE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: TERMINAL BLOCK (FLAT BASE TYPE)