

Recommended P.C.B Layout

MATERIAL

Insulator : 30% Glass fiber PBT
 Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.±
 .X ± 0.30
 .XX ± 0.20
 .XXX ±
 ANG ±



ORDER INFORMATION

H-R2514110030-1Xxx-LF
 SERIES | | | | LEADFREE
 | | | | 1X02:02WAY
 | | | | 1X40:40WAY
 DIP 90° | | | | DIP 3.0mm
 BASE 2.5mm | | | | CONTACT 11.0mm
 | | | | R/A 1.4mm

DESCRIPTION: PIN HEADER 2.54*2.54mm
 RIGHT ANGLE TYPE, SINGLE ROW OPPOSITE INSULATOR