

RECOMMENDED P.C.B. LAYOUT

### SPECIFICATIONS

#### ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.  
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.  
 Insulation Resistance:500 Medohms Minimum.at DC 500V.  
 Contact Resistance:25 Milliohms Maximum.  
 Operating Temperature:-55°C to+105°C.

#### MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.  
 Contact Separation Force:21 g.Minimum.  
 Grounding Screw Torque:3 Kg.Minimum.

#### MATERIALS:

Contacts:Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Shell:Cold Roller Steel.  
 Grounding Screw Torque:Brass

#### FINISHES:

Contact:Gold Flash.  
 Shell:Nickel Plated.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



#### ORDER INFORMATION

DCD106-PSZJ-09-LF

SERIES | | | | LEADFREE  
 | | | | 09 WAY  
 MALE | | JACKSCRW  
 | | CLIP  
 SEMI GOLD

DESCRIPTION: