

NOTE:

1.MATERIAL :

BASE : HIGH TEMPERATURE THERMOPLASTIC UL94V-0,
 TERMINAL:COPPER ALLOY,THICKNESS = 0.30 mm
 FORKLOCK:BRASS THICKNESS = 0.30 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
 SOLDER TAIL:150u"MIN MISTY TIN 50u" MIN NICKEL
 UNDERPLATE
 GOLD SPECIFICATION:SEE TABLE

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
 OPERATING TEMPERATURE: -40°C~+85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 焯倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ± 0.20
 .XX ± 0.15
 .XXX ±
 ANG ± 3°



ORDER INFORMATION

SATA-SWA038EZ-2+7+7-LF

SERIES | | | | LEADFREE
 | | | | 2+7+7 WAY
 FEMALE | | | | EAR+CLIP
 | | | | HIGH 3.85mm
 | | | | UPPER CONTACT
 | | | | 90°SMT

DESCRIPTION: USATA 16PIN母頭SMT帶螺絲孔型

www.morethanall.com