

## Material & Finish

### SHELL:

Steel  
Zinc plated, Tin plated  
or Nickel plated steel

### PIN CONTACT:

Phosphor bronze or Brass

### INSULATOR:

PBT & Glass-fibre reinforced  
UL-94-V0

### NUMBER OF CONTACT:

24,36,50

### CURRENT RATING:

1 Amp

### DIELECTRIC STRENGTH:

AC 500V Min.(for one minute)

### INSULATOR RESISTANCE:

1000MΩ Min. (at 500V DC)

### CONTACT RESISTANCE

25mΩ Max. mated

### TEMPERATURE:

-25° C to +85° C

△ Position

	A±0.25	B±0.13	C±0.13	D±0.20	E±0.25	F±0.25	G±0.25
24	54.70	46.78	23.76	45.68	35.50	37.50	45.88
36	67.80	59.74	36.72	58.65	51.50	53.75	58.85
50	82.80	74.85	51.84	73.75	68.50	70.90	73.95

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION



ORDER INFORMATION

CFM-S-xx-LF  
SERIES | LEADFREE  
24~50 WAY  
FEMALE

DESCRIPTION: 57 I.D.C. FOR FLAT CABLE  
FEMALE(METAL SHELL) ( 24 ~ 50 )