

NOTE :

1. SPECIFICATION:

- 1.1. CURRENT RATING: 0.5 Amp Max.
- 1.2. VOLTAGE RATING: 40 V ac (r.m.s) Max.
- 1.3. CONTACT RESISTANCE: 10m ohms Max.mated
- 1.4. INSULATION RESISTANCE: 100M ohms Min.
- 1.5. DIELECTRIC WITHSTANDING VOLTAGE:  
AC 500V Min. (for 1 minute)
- 1.6. OPERATION TEMPERATURE RANGE: -25° C ~ 85° C

2. MECHANICAL

- 2.1. INSERTION FORCE: 4.5KGF MAXMUM
- 2.1. WITHDRAWAL FORCE: 1.0KGF MINIMUM; 4.0KGF MAXMUM
- 2.3. DURABILITY: 10000 CYCLES AT 100 ± 50 CYCLES PERHOUR, CONTACT CHANCE FROM INITIAL VALUE: 30MINI Ohms MAX

"▲"为品管重点管控尺寸

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.25  
.XXX ± 0.15  
ANG ± 2°

P PROJECTION



ORDER INFORMATION

HDMI-PE16G-19-LF  
SERIES | LEADFREE  
19WAY  
METAL GOLD  
EDGE CLIP 1.6t  
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: HDMI-A-TYPE公座夹板1.6