

RECOMMENDED PCB LAYOUT
TOLERANCES: ±0.05


PIN NO.	PIN Assignmeng.
PIN1	DAT2
PIN2	CD/DAT3
PIN3	CMD
PIN4	VDD
PIN5	CLK
PIN6	VSS
PIN7	DAT0
PIN8	DAT1

MATERIALS

HOUSING: HIGH-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: STAINLESS STEEL
 HINGE: COPPER ALLOY NICKEL UNDER MATTE TIN PLATED
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA,
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.0 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50mΩ MAX
 INSULATION RESISTANCE: 1000MΩ MIN AT DC 500V
 OPERATION TEMPERATURE: -20°C~+85°C



RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ± 3°

PJECTION



ORDER INFORMATION

TFC-WHC-08-LF
 SERIES | | | LEADFREE
 | | | 08WAY
 | | | C / LAYOUT
 | | | HINGE
 | | | 90°SMT

DESCRIPTION: MICRO SD (T-FLASH), PCB MOUNT, SMT, METAL SHIELD, FEMALE, NON PUSH-PUSH TYPE(HINGE TYPE)

煜倫股份有限公司

www.morethanall.com