

PCB LAYOUT

**MATERIALS AND FINISH**  
 SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED  
 BACK SHELL TIN FINISHED  
 DIMPLES ON PLUG ONLY  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, WHITE COLOR  
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

**ELECTRICAL CHARACTERISTICS**  
 CONTACT CURRENT RATING : 7.5 AMPS  
 CONTACT RESISTANCE : 10 mΩ MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±



ORDER INFORMATION

DR72-P-09-LF  
 SERIES | LEADFREE  
 09WAY  
 MALE

DESCRIPTION: