

RECOMMENDED P.C.B LAYOUT FOR TOP ENTRY

Specifications  
 Current Rating:3Amp  
 Insulation Resistance:1000MΩMin.  
 Dielectric Withstanding Voltage:600VAC  
 Contact Resistance:20mΩMax.  
 Operating Temperature:-40°C to +105°C  
 Materials  
 Contact Material:Phosphor Bronze  
 Insulator Material:High Temperature Thermoplastic, UL 94V-0 Nylon 6T (無鹵) or the equivalent material

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.30

CHECKED BY GENIUS

.X ± 0.25

UNIT / mm

SCALE 1 : 1

.XX ± 0.15


.XXX ± 0.10

ANG ±

DATE

SIZE A4

PJECTION



ORDER INFORMATION

F-Z37XC-2Xxx-LF

SERIES | LEADFREE  
 2X02:04WAY  
 2X40:80WAY  
 BOTTOM ENTRY SMT | CAP  
 NON POST  
 HIGH 3.65mm

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54 FEMALE HEADER DUAL ROWS SMT TYPE CONNECTOR