



N=Number of 1/2poles

Dim A=N×6.35
Dim B=(N-1)×6.35

Poles	Dim A Tol	Dim B Tol
2×2P-2×8P	±0.30	±0.30
2×8P-2×16P	±0.40	±0.40

Material:

- Item 1 Insulator body:Thermoplastic (UL 94V-0)
- Item 2 Terminal body(house): Brass ,Ni plated
- Item 3 Contacts:Brass ,Tin plated
- Item 4 Terminal screw: Steel Zinc plating"-slot type

Electrical

- Voltage rating: 300VAC
- Current rating: 30A
- Wire range:
- Solid wire(AWG): 10-30
- Stranded wire(AWG): 10-30
- ▲ Torque(Lb-In): 5.2
- ▲ Screw: M3.5
- Wire strip length: 10-11mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- ▲ Soldering temperature: 250°C±10°C/5 Sec
- Safety approval: us

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

TBH063B1-D21R-xx-LF

SERIES

LEADFREE
POS PER ROW
02:02 WAY
16:16 WAY
R TYPE FOOT
HIGH 21.5mm

DIP 180°

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com