



A	COLOR	B
1	YELLOW	13, 14, 15
4	YELLOW	
2	BLACK	4, 5, 6
3	BLACK	10, 11, 12

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #20 YELLOW	2PCS	E108485
2	WIRE:	UL1007 #20 BLACK	2PCS	E108485
3	HOUSING:	MIF-SH-1X04	1PCS	E115256
4	TERMINAL:	MIF-FT-20	4PCS	
5	HOUSING:	SATA-PS-15	1PCS	E149293
6	H. S TUBE:	2Φ*10mm BLACK F32	2PCS	
7	H. S TUBE:	3.5Φ*10mm BLACK F32	1PCS	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

MIFSATA-041520-A12N-LF

SERIES

LEADFREE
304.8mm
FEMALE TO MALE
20 AWG
04 TO 15 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS'Y