

Specification

- 1.Current Rating:3A AC/DC
- 2.Voltage Rating:250V AC/DC
- 3.Contact Resistance:20mΩ Max.
- 4.Insulation Resistance:1000MΩ Min. At DC 500V
- 5.Dielectric Withstanding Voltage:AC 1000V/Minute
- 6.Operating Temp.:−25°C~+85°C

Material:

- 1.Housing:Thermoplastic PA66 UL94V-0
- 2.Contact Pin:Copper Alloy SQ. Pin 0.64mm

Finish:

Contact Pin:Bright Tin Plated.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ± 0.35
.XX ± 0.25
.XXX ± 0.15
ANG ±



ORDER INFORMATION

MKL-DP3-04W3-LF
SERIES | | | LEADFREE
| | | 3 WAY WALL
| | | 04 WAY
| | | #3 POST
| | | DIP180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Wire To Board Wafer 2.54mm 180° DIP With Post