

P.C.B. LAYOUT

NOTES:

1. Rating: 300V 8A
PITCH: 3.81mm
2. Insulation Withstands Voltage:
AC 1000V/MIN
3. Insulation Resistance:
1000MΩ or more at DC500V
4. Using Temperature Range:
-40°C~+110°C
5. Undimensioned Tolerances:

—	∩	□	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONS TOLERANCES			±0.3

P	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36
U	3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.1	41.91	45.72	49.53	53.34	57.15	60.96	64.77
V	9.01	12.52	16.63	20.44	24.25	28.06	31.87	35.68	39.49	43.3	47.11	50.92	54.73	58.54	62.35	66.16	69.97

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

TBH038B1-PRC05-xx-LF

SERIES

MALE

0.5"

CAGE

DIP 90°

LEADFREE

04:04PIN PER ROW

36:36PIN PER ROW

DESCRIPTION:

www.morethanall.com