



P.C.B LAYOUT
BOTTOM VIEW
P.C.B Tolerance ±0.1

USB Connector Termination Assignment

CONTACT NUMBER	SIGNAL NAME
1,5	VBUS
2,6	D-
3,7	D+
4,8	GND
SHELL	SHIELD

NO	PART NAME	QTY	MATERIAL	PLATING & COLOR
6	SHIELD	2	BRASS	Ni, t=0.3mm
5	CONTACTS(DIN)	6	COPPER ALLOY	GOLD 3-5u" AT CONTACT AREA LEAD FREE TIN ALLOY AT TERMINATION. NICKEL OVER ALL.
4	CONTACTS(USB)	8	COPPER ALLOY	GOLD 3-5u" AT CONTACT AREA LEAD FREE TIN ALLOY AT TERMINATION. NICKEL OVER ALL.
3	COVER	1	P. B. T	BLACK
2	HOUSING(DIN)	1	P. B. T	Purple (PAN 2715C)
1	HOUSING(USB)	1	P. B. T	BLACK

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

MDUB-FRPP-06AA-LF

SERIES | LEADFREE
4PIN A TO A TYPE
06PIN MINI DIN
PURPLE
DIP 90°
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: