

Material: Post: Brass, Tin/Plated  
 Base: Nylon 66, UL94V-2  
 Qty: 500 pcs/bag

### SPECIFICATIONS

Accepts cantilever crimp terminal  
 Housing Nylon 66 (UL94V-2)  
 Mates with 0.084" (2.13mm) crimp terminal housing  
 Terminal Retention to housing-8lbs (3.63kg) min.  
 Voltage: rating: AC, DC, 250V  
 Current rating: 7A, AC, DC  
 Withstand voltage: 1500V AC/minute  
 Insulation resistance: 1000M $\Omega$  min  
 Temperature range: -25 $^{\circ}$ C~+90 $^{\circ}$ C  
 Contact resistance: Initial Valueable/10m $\Omega$  max.  
 After environmental testing/20m $\Omega$  max.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

P PROJECTION

X,  $\pm$   
 .X  $\pm$  0.30  
 .XX  $\pm$  0.20  
 .XXX  $\pm$  0.10  
 ANG  $\pm$  2 $^{\circ}$



ORDER INFORMATION

DP-PDS-04-LF  
 SERIES | RIB | LEADFREE  
 04WAY  
 DIP 180 $^{\circ}$   
 MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: PITCH 5.08 DISK DRIVER POWER CONNECTOR SYSTEM