



NOTES

1.MATERIAL

- 1.1 Insulator: P.B.T+15% G.F(UL94V-0)
- 1.2 Contact: Phosphor Bronze

2.SPECIFICATION

- 2.1 Current Rating: 1 Amp
- 2.2 Current Voltage: 30V RMS Max
- 2.3 Dielectric Withstanding: AC 500V min Per minute
- 2.4 Insulation Resistance: 500M ohms min At DC 500V
- 2.5 Contact Resistance: 20m ohms Max
- 2.6 Operating Temperature: -45°C ~ 105°C
- 2.7 Insertion force: 0.5Kgf/pin MAX.
- 2.8 Withdrawal force: 0.1Kgf/pin MIN.

"*"標示是重點管控尺寸

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ± 0.15
ANG ± 2°

PPOJECTION



ORDER INFORMATION

J-B-04-LF
SERIES | LEADFREE
HIGH 4.5mm
OPEN TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MJ 4.5B黑磷銅半面金 RoHS